



### Applications and Key Benefits

- + AGM standby batteries 25Ah to 2000Ah, designed for highest integrity, security and reliability  
Ideal for:
  - High rate discharge UPS application
  - Telecom wireless and wireline
  - Industry and process controls
  - Emergency power supply systems
  - IT network operations and data centers
  - Electric utility
  - Switchgear
- + 2V cells and 4V, 6V and 12V blocs
- + Excellent for high rate discharge (1 to 60 min) and medium to very long discharge (2 to 20 hours)
- + >12 years design life in float operation in temperature controlled environments
- + Very high energy density allows more compact battery layout and footprint
- + Flame retardant plastics and flashback protection
- + Full compliance with international product and safety specifications
- + VRLA AGM and gas recombination technology with 99% internal recombination
- + No separate battery room required
- + Maintenance free without topping-up
- + Non-hazardous for sea/rail/ road transportation
- + 100% Recyclable



### Applicable Standards

- IEC 60896 Part 21 - VRLA methods of testing
- IEC 60896 Part 22 - VRLA requirements
- Eurobat "Long Life" - 12 years and longer
- BS 6290 Part 4 - specifications for VRLA classification
- BS 6334 / UL 94 V0 / IEC 707 FV0 determination of materials flammability
- Bellcore TR-NWT-000766 - VRLA battery generic requirements
- Bellcore TR-NWT-000909 - Fiber generic requirements
- Telcordia GR-4228 - VRLA battery string certification
- UL Recognized
- UL 1778 - UPS equipment

### FIAMM Manufacturing

- ISO 9001 Quality Management System
- ISO 14001 Environmental Management System

### Technical Features

- Extra-thick plates with grids cast from high purity lead-calcium-tin alloy to minimize grid growth and corrosion, for prolonged service life
- Electrolyte absorbed in glass mat "AGM" separators with extremely high micro porosity
- Threaded post terminals with brass inserts guarantee highest conductivity, maximum torque retention and easy installation
- Heavy-duty internal straps and through-the-partition cell connections minimize internal resistance
- State of the art post seals prevent acid seepage over a wide temperature range
- Cells equipped with one-way safety valves to allow excess gas to escape when overcharging
- Flame arrestors prevent sparks or flames from entering the battery
- ABS IEC 707 FV0 and UL 94 V0 (LOI greater than 28%) flame retardant plastics
- Thick walled plastics designed for unsurpassed mechanical strength
- Most sizes have integrated handles
- < 2% self-discharge per month at 20°C allows 6 months shelf life
- Remote venting system available for applications which require limited gassing to be vented externally

## FIAMM SLA range

BATTERY TYPE	NOMINAL VOLTAGE (V)	CAPACITY (AH) at 20°C	SHORT CIRCUIT CURRENT (A)	DC INTERNAL RESISTANCE (mohm)	DIMENSIONS (mm)			WEIGHT (kg)
		10 hrs to 1.80 VPC	IEC 60896-21	IEC 60896-21	Length	Width	Height	
12 SLA 25	12	25	1150	11	218	129	166	11
12 SLA 30	12	30	1300	9.0	200	138	190	14
12 SLA 50	12	50	2030	6.0	288	173	202	21
12 SLA 80	12	80	3000	4.0	360	164	228	29
6 SLA 100	6	100	3800	1.7	271	173	202	20
6 SLA 125	6	125	4300	1.4	268	172	230	24
4 SLA 150	4	150	5000	0.70	271	173	202	19
6 SLA 160	6	160	3050	1.96	298	202	226	32
6 SLA 180*	6	180	3400	1.75	387	173	251	35
6 SLA 200	6	200	3700	1.58	250	125	366	36
4 SLA 200	4	200	3800	1.0	250	202	226	26
2 SLA 250	2	250	5900	0.35	271	173	202	17
2 SLA 300	2	300	6300	0.32	271	173	202	19
2 SLA 330	2	330	7500	0.27	208	195	230	22
2 SLA 405/4*	2	405	7600	0.26	250	202	226	27
2 SLA 500*	2	500	9700	0.21	387	173	251	34
2 SLA 580*	2	580	10800	0.19	387	173	251	37
2 SLA 800**	2	820	9700	0.206	254	210	525	64
2 SLA 1000**	2	1025	12000	0.165	254	210	525	74
2 SLA 1500**	2	1500	16000	0.125	275	210	660	110
2 SLA 2000**	2	2000	20000	0.102	368	218	660	143

\* The front view is the short side

\*\* This cell must be installed horizontally

### Electrical Characteristics

- FLOAT VOLTAGE CHARGE AT 20°C: 2.27 V/cell.
- TEMPERATURE COMPENSATION: -2.5 mV/cell/°C
- SELF-DISCHARGE AT 20°C: < 2% / month